

Amendment dated 7/9/2007  
Reply to Office Action mailed on 5/9/2007

Application No. 10/774,780  
Docket No. Z-3603/Case 8144

### AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1.-21. (Cancelled)
22. (Currently Amended) A method of making a shaving razor, the method comprising
- providing a housing including a generally rectangular recess having four side walls and carrying a guard member,
  - providing a plurality of elongated metal razor blades, each blade having a cutting edge and first and second longitudinal ends,
  - securing said first longitudinal ends to a first plastic block and said second longitudinal ends to a separate second end block [[at locations]] in slots on said first and second plastic blocks such that said cutting edges collectively define a shaving surface, and said blades and blocks provide an integrated blade subassembly, wherein no part of said integrated blade subassembly extends beyond an outer surface of said blocks, and
  - inserting said integrated subassembly into the rectangular recess wherein said guard member is in front of said blades.
- 23.-27. (Cancelled)
28. (Previously presented) The method of claim 22 wherein said recess is open to the top, and said positioning involves lowering said integrated blade subassembly into said recess.

Amendment dated 7/9/2007  
Reply to Office Action mailed on 5/9/2007

Application No. 10/774,780  
Docket No. Z-3603/Case 8144

29. (Currently Amended) A shaving razor comprising  
a housing defining a generally rectangular recess having four side walls  
and carrying a guard member, and, within and surrounded by the side walls of the  
housing,  
a blade subassembly comprising  
a plurality of elongated metal blades, each said blade having a  
cutting edge, said cutting edges collectively defining a shaving surface,  
and each said blade having first and second longitudinal ends, and  
first and second plastic blocks, said first longitudinal ends being  
secured to said first plastic block and said second longitudinal ends being  
secured to said second plastic block, said first plastic block being separate  
from said second plastic block, to provide an integral unit, said blades  
being secured to each other only at their ends, wherein said first and  
second longitudinal ends are received in slots in said first and second  
plastic blocks and wherein no part of the blade subassembly extends  
beyond an outer surface of said blocks and wherein said guard member is  
in front of said blades.
30. (Cancelled)
31. (Cancelled) The razor of claim 29 wherein said first and second longitudinal ends  
are received in slots in said first and second plastic blocks.
32. (Previously presented) The razor of claim 31 wherein said first and second  
longitudinal ends and said slots have mating locking structure to secure said first  
and second longitudinal ends to said first and second plastic blocks.
33. (Currently Amended) The razor of claim ~~[[33]]~~ 32 wherein said locking structure  
includes projections projecting into said slots that engage holes through said  
longitudinal ends.

Amendment dated 7/9/2007  
Reply to Office Action mailed on 5/9/2007

Application No. 10/774,780  
Docket No. Z-3603/Case 8144

34. (Currently Amended) The razor of claim [[34]] 33 wherein said longitudinal ends have a thickness that is greater than the width of the slot minus the height of the projection.
35. (Previously presented) The razor of claim 29 wherein each said blade includes an elongated cutting member having said cutting edge and a said first longitudinal end and a said second longitudinal end.
36. (Previously presented) The razor of claim 29 wherein said plurality of elongated metal blades includes at least three said blades.
37. (Previously presented) The razor of claim 29 wherein said plurality of elongated metal blades includes at least four said blades.
38. (Currently Amended) A method of making a shaving razor, the method comprising  
providing a housing including a generally rectangular recess having four side walls,  
providing a plurality of elongated metal razor blades, each blade having a cutting edge and first and second longitudinal ends,  
securing said first longitudinal ends to a first plastic block and said second longitudinal ends to a second end block [[at locations]] in slots on said first and second plastic blocks such that said cutting edges collectively define a shaving surface, and said blades and blocks provide an integrated blade subassembly consisting of said first plastic block, said second end block and said blades,  
wherein no part of said integrated blade subassembly extends beyond an outer surface of said blocks, and  
inserting said integrated subassembly into the rectangular recess.
39. (Currently Amended) The method of claim [[1]] 22 further comprising a lubricating strip carried by said housing.

Amendment dated 7/9/2007  
Reply to Office Action mailed on 5/9/2007

Application No. 10/774,780  
Docket No. Z-3603/Case 8144

40. (Currently Amended) A shaving razor comprising  
a housing defining a generally rectangular recess having four side walls,  
and, within and surrounded by the side walls of the housing,  
a blade subassembly consisting of  
a plurality of elongated metal blades, each said blade having a  
cutting edge, said cutting edges collectively defining a shaving surface,  
and each said blades having first and second longitudinal ends, and  
first and second plastic blocks, said first longitudinal ends being  
secured to slots in said first plastic block and said second longitudinal ends  
being secured to slots in said second plastic block to provide an integral  
unit, said blades being secured to each other only at their ends,  
wherein no part of the blade subassembly extends beyond an outer surface of said  
blocks.
41. (Previously Presented) The shaving razor of claim 29 further comprising a  
lubricating strip carried by said housing.
42. (Previously Presented) The shaving razor of claim 41 wherein said guard is  
positioned adjacent one wall of the recess and said lubricating strip is positioned  
adjacent an opposite wall of the recess.